

keep a **SharpEye™** on your safety



40/40L-LB

UV-IR Flame Detector Series

Maximum choice of features in a high performance package



SharpEye™

Model 40/40L (or LB, with Built-in-test option) provides a combination of UV and IR sensors, where the IR sensor operates at a wavelength of 2.5-3.0 μm , and can detect hydrocarbon-based fuel and gas fires, hydroxyl and hydrogen fires, as well as metal and inorganic fires.

The UV/IR flame detector senses radiant energy in the short wave section of both the ultraviolet and infrared portions of the electromagnetic spectrum. The signals from both sensors are analyzed for frequency, intensity and duration. Simultaneous detection of radiant energy in both the UV and IR sensors triggers an alarm signal.

The UV sensor incorporates a special logic circuit that helps prevent false alarms caused by solar radiation.

Due to increased reliability, the 40/40 Series warranty period has been extended to 5 years and is SIL2 (TUV) approved to IEC 61508.

FEATURES & BENEFITS

- UV/IR Dual-Sensor
- Solar blind
- Automatic Built-In-Test (BIT) and Manual - to assure continued reliable operation (in 40/40LB only)
- Heated window - for operation in harsh weather conditions (snow, ice, condensation)
- Multiple output options for maximum flexibility and compatibility
 - Relays (3) for Alarm, Fault and Auxiliary
 - 0-20mA (stepped)
 - HART Protocol for maintenance and asset management
 - RS-485, Modbus Compatible
- High Reliability - MTBF - minimum 150,000 hours
- Approved to Safety Integrity Level 2 (SIL2 – TUV) model 40/40LB only
- 5-Year Warranty
- User Programmable via HART or RS-485
- Hazardous area zones:
 - Zones 1 & 2 with IIC gas group vapors present
 - Zones 21 & 22 with IIIC dust type present
- Ex approved to:
 - ATEX & IECEx
 - FM/FMC/CSA
 - TR CU (EAC)
- 3rd party performance approved
 - EN54-10 (VdS)
 - FM3260
- Marine Approval
 - MED 'Wheelmark' approval (DNV)

APPLICATIONS (model dependent)

Offshore Oil & Gas installations	Pharmaceutical Industry
Onshore Oil & Gas installations and pipelines	Printing Industry
Chemical plants	Warehouses
Petrochemicals plants	Automotive Industry
Storage Tank farms	Explosives & Munitions
Aircraft hangars	Waste Disposal facilities
Power Generation facilities	Aerospace Industry
	Paint, Polymer and Glue processes

keep a **SharpEye™** on your safety

GENERAL SPECIFICATIONS

Spectral Response	UV: 0.185 - 0.260 μm; IR: 2.5-3.0 μm					
Detection Range (at highest Sensitivity Setting for 1ft ² (0.1m ²) pan fire)	Fuel	ft / m	Fuel	ft / m	Fuel	ft / m
	n-Heptane	50 / 15	Kerosene	37 / 11	Methane*	26 / 8
	Gasoline	50 / 15	Methanol	25 / 7.5	LPG*	43 / 13
	Diesel Fuel	37 / 11	IPA (Isopropyl Alcohol)	25 / 7.5	Polypropylene Pellets	33 / 10
	JP5	37 / 11	Hydrogen*	33 / 10	Office Paper	16 / 5
	Alcohol 95%	25 / 7.5	* 30" (0.75m) high, 10" (0.25m) width plume fire			
Response Time	Typically 5 seconds					
Adjustable Time Delay	Up to 30 seconds					
Sensitivity Ranges	1 ft ² (0.1m ²) n-heptane pan fire from 50 ft (15m)					
Field of View	Horizontal 100°; Vertical 95°					
Built-in-Test (BIT)	Automatic (and Manual)					
Temperature Range	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)					
Humidity	Up to 95% non-condensing (withstands up to 100% RH for short periods)					
Heated Optics	To eliminate condensation and icing on the window					

ELECTRICAL SPECIFICATIONS

Operating Voltage	24 VDC nominal (18-32 VDC)
Power Consumption	Standby: Max. 90mA (110mA with heated window) Alarm: Max. 130mA (160mA with heated window)
Cable Entries	2 x 3/4" - 14NPT conduits or 2 x M25 x 1.5 mm ISO
Wiring	12 - 22AWG (0.3mm ² - 2.5mm ²)
Electrical Input Protection	According to MIL-STD-1275B
Electromagnetic Compatibility	EMI/RFI protected to EN61326-3 and EN61000-6-3
Electrical Interface	The detector includes twelve (12) terminals with five (5) wiring options (factory set)

OUTPUTS

Relays	Alarm, Fault and Auxiliary SPST volt-free contacts rated 2A at 30V DC
0-20mA (stepped)	Sink (source option) configuration Fault: 0 +1mA IR: 8mA ± 5% Alarm: 20mA ± 5% BIT Fault: 2mA ± 10% UV: 12mA ± 5% Resistance Loop: 100-600 Ω Normal: 4mA ± 10% Warning: 16mA ± 5%
HART Protocol	Optional HART communications on the 0-20mA analog current (FSK) - used for maintenance, configuration changes and asset management, available in mA source output wiring options
RS-485	RS-485 Modbus compatible communication link that can be used in computer controlled installations

MECHANICAL SPECIFICATIONS

Materials	- Stainless Steel 316L with electro polish finish
Enclosure options	- Heavy duty copper free aluminum (less than 1%), red epoxy enamel finish (not available in FM version)
Mounting	Stainless Steel 316L with electro polish finish
Dimensions	Detector 4" x 4.6" x 6.18" (101.6 x 117 x 157 mm)
Weight	Detector (St.St.) 6.1 lb (2.8 kg) Tilt mount 2.2 lb (1.0 kg) Detector, aluminum 2.8 lb (1.3 kg)
Environmental Standards	Meets MIL-STD-810C for Humidity, Salt & Fog, Vibration, Mechanical Shock, High Temp, Low Temp
Water and Dust	IP66 and IP67 per EN60529, NEMA 250 6P

APPROVALS

Hazardous Area	ATEX and IECEx	Ex II 2 G D Ex db eb op is IIC T4 Gb Ex tb op is IIIC T96°C Db (-55°C ≤ Ta ≤ +75°C)	Ex db eb op is IIC T4 Gb Ex tb op is IIIC T106°C Db (-55°C ≤ Ta ≤ +85°C)
	FM/FMC/CSA	Class I Div. 1, Groups B, C & D Class II/III Div. 1, Groups E, F & G	
	TR CU (EAC)	1 Ex db eb op is IIC T4 Gb X Ex tb op is IIIC T96°C Db X (-55°C ≤ Ta ≤ +75°C)	1 Ex db eb op is IIC T4 Gb X Ex tb op is IIIC T106°C Db X (-55°C ≤ Ta ≤ +85°C)
Performance	EN54-10 (VdS) FM3260		1 Ex db eb mb op is II T4 Gb X Ex tb op is IIIC T98°C Db X (-55°C ≤ Ta ≤ +75°C)
Reliability	IEC61508 - SIL2 (TUV) - model 40/40LB only		
Marine	MED 'Wheelmark' approval (DNV)		

ACCESSORIES

Flame Simulator FS-1200	U-Bolt/Pole Mount	789260-2 (2" pole)	Air Shield	777650	Weather Cover 777163 (St.St) *777263 (Plastic)
Tilt Mount 40/40-001		789260-1 (3" pole)			
Duct Mount 777670	USB RS485 Harness Kit	794079			
	E.O.L Encapsulated Resistor	777915-X			

*Supplied free of charge with the detector