UL Product **iQ**[™]

VNIV.EX26743 - SPRINKLERS, AUTOMATIC AND OPEN

Sprinklers, Automatic and Open

See General Information for Sprinklers, Automatic and Open

GREEN FIRE ENGINEERING LTD

BUILDING 70, BAY 3, THIRD AVE PENSNETT TRADING ESTATE KINGSWINFORD, DY6 7FE UNITED KINGDOM Sprinkler Identification Number (SIN), Glass Bulb Type GF80SU, GF80QU, GF80SP, GF80QP, GF80SC, GF80QC, GF80SH and GF80QH.

UPRIGHT AND PENDENT STANDARD-SPRAY SPRINKLERS NOMINAL 5.6 K-FACTOR

SIN	Response Type	Туре	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
GF80SU	SR	Upright	5.6	175	135, 155, 175, 200
GF80QU	QR	Upright	5.6	175	135, 155, 175, 200
GF80SP	SR	Pendent	5.6	175	135, 155, 175, 200
GF80QP	QR	Pendent	5.6	175	135, 155, 175, 200

STANDARD SIDEWALL-SPRAY SPRINKLERS

Response			Nom	System Working	
SIN	Туре	Туре	K-Factor	Pressure, psig	Temp Rating, °F
GF80SH*#	SR	Horizontal	5.6	175	135, 155, 175, 200
GF80QH*#	QR	Horizontal	5.6	175	135, 155, 175, 200

* - Installed 4 to 6 in. below ceiling.

- For ordinary hazard occupancies.

FLUSH, RECESSED, AND CONCEALED SPRINKLERS

Response			Nom		Temp Rating, °F	
SIN	Туре	Туре	K-Factor	Cover	Sprinkler	
GF80SC	SR	Concealed	5.6	135, 155	135, 155, 175, 200	
GF80QC	QR	Concealed	5.6	135, 155	135, 155, 175, 200	

Last Updated on 2017-06-12

ሠ

EX26743

SPRINKLERS, AUTOMATIC AND OPEN | UL Product iQ

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"