

Analogue Dual Relay Controller

ST-RC2B-SC



Features

- ▶ Loop powered
- ▶ Single loop address
- ▶ 2 Independently controlled changeover relays
- ▶ Relays contact rated at 30 V dc at 1 A
- ▶ Auxiliary monitored input
- ▶ DIN-Rail version available
- ▶ Both models feature an integral short-circuit isolator
- ▶ Both models approved by LPCB

Description

Model ST-RC2B-SC is a Dual Relay Controller designed to provide two general-purpose relay outputs, each output can be driven separately for control of such devices as dampers or for control of plant and equipment shutdown. The monitored input can be used for local power supply fault monitoring or as a general-purpose input.

The unit is also available as a DIN Rail mountable version; both models feature an integral short-circuit isolator. The ST-RC2B-SC utilises simple DIL switches for reliable addressing. A back box is also available (ST-MBB) which, when used in conjunction with the ST-RC2B-SC, increases the IP rating to IP65.

Specification

Order codes*1		ST-RC2B-SC		(module with SCI)
		ST-RC2B-SC (HFP)		
		ST-RC2D-SC		(DIN module with SCI)
		ST-RC2D-SC/(HFP)		
Operating voltage		17 - 41 V dc		
Low Power Mode (0.75s)		170 μA		
Quiescent current		300 μA		
Current consumption		22 mA ± 20 % (polling)		
Current in short-circuit		8 mA		
Maximum short-circuit current		1 A (loop)		
Relay Contact Rating		30 V dc max, 1 A (resistive load)		
Input E.O.L. resistor		10 kΩ, ±5%, 0.25 W		
Input threshold level		ON=470 Ω, Short cct <50 Ω, Open cct >100 KΩ		
Operating Temperature Range		-10 °C to +50 °C		
Storage Temperature Range		-30 °C to +60 °C		
Maximum Humidity		95%RH Non Condensing (at 40°C)		
Weights (g) & Dimensions (mm)	Module Enclosure	343	L=157 x W=127 x D=35 (Module & Lid) D=79 (Module, Lid & ST-MBB) (add 235 to module weight when using ST-MBB)	
	DIN Enclosure	124	L=119 x W=108 x D=24	
Colour and enclosure material		ST Module & ST-MBB White ABS, DIN Module Green ABS, Module Lid Semi-Opaque Black ABS as standard (white version – ST-MBBC(WHT) also available)		

*1 Fire alarm control panel compatibility required for these products.

Silver-Tec Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Silver-Tec Ltd. to be a complete and up-to-date description.